



# UNDERGROUND MARKING TAPE

## Manufacturing Specification Data Sheet

# STANDARD NON-DETECTABLE

<u>Property</u>	<u>Test Method</u>	<u>U.S. Value</u>	<u>Metric Value</u>
Overall Thickness	ASTM D-2103	4.0 Mil (Nominal)	0.1 mm
Weight	ASTM D-2103	18.0 lbs/1000 ft <sup>2</sup>	8.8 kg/100 m <sup>2</sup>
Tensile Strength	ASTM D-882	3250 PSI 11.7 lbs/ in width	22.4 MPa 52.0 N
Elongation	ASTM D-882	650%	650%
Printability	ASTM D-2578	> 40 dynes	> 40 dynes

### Key Features and Benefits

- \* Single layer polyethylene film
- \* Identifies and protects buried lines
- \* Suitable for open trench applications
- \* Lead-free pigments maintain color vibrancy in the soil
- \* Environmentally safe ink ensures long lasting warning message
- \* Acid and alkali resistance enhances long term integrity in the ground
- \* Meets American Public Works Association (APWA) National Color Code
- \* Offered in blue, green, yellow, red, orange, and purple with black lettering

### Approvals

- \* U.S. DOT, Office of Pipeline Safety
- \* NTSB, Prevention of Damage to Pipeline Study
- \* OSHA, Location of Underground Utility Lines Regulation
- \* API, Recommended Practice For Marking Buried Petroleum Pipelines
- \* GSA, Public Buildings Mechanical & Electrical Equipment Specification
- \* REA, National Electrical Safety Code for Underground Construction



IN STOCK NOW! Inc., P.O. Box 101, Lake Mills, WI 53551

920-648-3844 (Phone)

920-648-2646 (Fax)

[www.instocknowinc.com](http://www.instocknowinc.com)

[sales@instocknowinc.com](mailto:sales@instocknowinc.com)